

Printing date 11.12.2019 Version number 1 Revision: 11.12.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: <u>DAI-EL G-522,G-551,G-556,G-557,G-558,G-565</u> Synonyms: G-522, G-551, G-556, G-557, G-558, G-565

1.2 Relevant identified uses of the substance or mixture and uses advised against: Rubber compounding

1.3 Details of the supplier of the safety data sheet DCC-30001

Manufacturer/Supplier:

DAIKIN FLUOROCHEMICALS(CHINA) CO.,LTD

NO.8 JinYu Road(West)Advanced Materials Industrial Park, Changshu, Jiangsu 215522, China

TEL:(+86)512-5232-2266 *FAX:*(+86)512-5232-2366

Further information obtainable from: http://www.daikinchem.com.cn

1.4 Emergency telephone number: +86-512-5232-0949

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

The substance is not classified, according to the CLP regulation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008: Not applicable

Signal word: Not applicable **Additional information:**

EUH210 Safety data sheet available on request.

SECTION 3: Composition/information on ingredients

Information on ingredients:

CAS: 25190-89-0 Vinylidene fluoride-tetrafluoroethylene-hexafluoropropylene copolymer >97%

CAS: 1478-61-1 Bisphenol AF <2%

CAS: 49663-94-7 DBU-B <1%

Eye Irrit. 2, H319

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Seek medical treatment.

After inhalation: In case of inhaling decomposed gases: supply fresh air and consult a doctor in case of complaints. After skin contact:

Immediately wash with water and soap and rinse thoroughly.

After contact with the molten product, cool rapidly with cold water.

Do not pull solidified product off the skin.

Immediately rinse with warm water and soap.

Consult a doctor in case of complaints.

After eye contact:

Rinse opened eye for several minutes under running water.

Consult an ophthalmologist in case of complaints.

After swallowing: If symptoms persist consult a doctor.

4.2 Most important symptoms and effects, both acute and chronic: No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: No further information available.



Printing date 11.12.2019 Version number 1 Revision: 11.12.2019

Trade name: DAI-EL G-522, G-551, G-556, G-557, G-558, G-565

5.2 Special hazards arising from the substance or mixture:

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters:

Protective equipment:

Wear self-contained breathing apparatus and protective suit.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation before entering the area.

Keep out unauthorized persons.

Wear appropriate protective devices (See Section 8 Exposure Controls/Personal Protection).

Avoid contact with eyes and skin.

Do not swallow the product.

6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

6.3 Methods and material for containment and cleaning up: Pick up mechanically.

6.4 Reference to other sections:

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Extractors are required on all machines used for thermal processing or powder handling processes.

Do not handle until all safety precautions have been read and understood.

Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities:

Storage

Requirements to be met by storerooms and receptacles: Store in a cool and dry location.

Information about storage in one common storage facility:

See section 10 for information on incompatible materials.

Further information about storage conditions:

Protect from heat and direct sunlight.

Store containers in a well ventilated area.

7.3 Specific end use(s): No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters No further information available.

Ingredients with limit values that require monitoring at the workplace: Not required.

8.2 Exposure controls

Personal protective equipment

General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not eat or drink while working.

Do not smoke.

Respiratory protection: Dust respirator, simplified dust respirator

Protection of hands:



Material of gloves: Rubber



Printing date 11.12.2019 Version number 1 Revision: 11.12.2019

Trade name: DAI-EL G-522, G-551, G-556, G-557, G-558, G-565

Eye protection:



Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance

Form: Solid

Colour: Whitish - light yellow

Odour: Odourless
Odour threshold: Not determined.

pH-value: No further information available.
 Melting point/freezing point: No further information available.
 Initial boiling point and boiling range: No further information available.

Flash point: Not applicable.

Flammability (solid, gas): Product is not flammable.

Decomposition temperature: >230 °C (1%TG) **Auto-ignition temperature:** Not determined.

Explosive properties: Product does not present an explosion hazard.

Explosion limits:

Lower explosive limit:No further information available.Upper explosive limit:No further information available.Vapour pressure:No further information available.

Density at 25 °C:1.8-2.1 g/cm³Relative densityNot determined.Vapour densityNot applicable.Evaporation rateNot applicable.

Solubility in / Miscibility with

water: Insoluble.

Partition coefficient: n-octanol/water: No further information available.

Viscosity:

Dynamic:Not applicable.Kinematic:Not applicable.

9.2 Other information: No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: To avoid thermal decomposition do not overheat.

10.3 Possibility of hazardous reactions: No dangerous reactions known under normal conditions of use.

10.4 Conditions to avoid: Keep away from heat, sparks, flame, high temperature.

10.5 Incompatible materials:

Metal powder (e.g. Al, Mg) and fluorine oxidizer. There is a danger of chemical reactions that could cause fire or explosion when the product is heated with them.

10.6 Hazardous decomposition products:

As for decomposition products, particulate matters and extremely toxic/corrosive fumes may be generated (HF, carbonyl fluoride, monomers, perfluoroisobutylene).

Decomposition products differ depending on the temperature and conditions.



Printing date 11.12.2019 Version number 1 Revision: 11.12.2019

Trade name: DAI-EL G-522, G-551, G-556, G-557, G-558, G-565

Organic iodine compounds such as methyl iodide may be generated when iodine which becomes a crosslinking point reacts with decomposed products of organic peroxide.

SECTION 11: Toxicological information

11.1 Information on toxicological effects No futher information available.

Acute toxicity no data

LD/LC50 values relevant for classification: No further information available.

Primary irritant effect

Skin corrosion/irritation No further information available.

Serious eye damage/irritation No further information available.

after inhalation: No further information available.

Respiratory or skin sensitisation No further information available.

Other information (about experimental toxicology): No further information available.

Subacute to chronic toxicity No further information available.

Additional toxicological information:

General effects:

Fumes generated during burning may cause "polymer fume fever" (flu-like symptons such as fever, chill, cough).

This may last for a whole day and night.

Fumes are not absorbed in skin. No sensitizing effect known.

Effects of hydrogen fluoride:

Low concentration of hydrogen fluoride may cause feeling of dyspnea, cough, irritation in eyes, nose, throat, fever, chill for 1-2 days.

After that, dyspnea, cyanosis and pulmonary edema may be seen.

High concentration of hydrogen fluoride damages liver and kidney.

Effects of carbonyl fluoride: Skin: Irritation or eruption Eye: Ulcer in cornea, conjunctiva Respiratory system: Irritation

Lung: Temporary symptons such as cough, pain, dyspnea

Persons who have experienced lung diseases are vulnerable to toxicity caused by excessive exposure to pyrolysis products

CMR effects

Germ cell mutagenicity

Not applicable

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability: The product is thought to be non-biodegradable.

12.3 Bioaccumulative potential: No further relevant information available.

12.4 Mobility in soil: No further relevant information available.

Ecotoxical effects: no data

12.5 Results of PBT and vPvB assessment

PBT: No data vPvB: No data

12.6 Other adverse effects: No further relevant information available.



Printing date 11.12.2019 Version number 1 Revision: 11.12.2019

Trade name: DAI-EL G-522, G-551, G-556, G-557, G-558, G-565

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation:

Landfill disposal is recommended.

In case of incineration, the temperature must be higher than 800 $^{\circ}$ C.

Treat exhaust gas such as HF in a suitable way.

Disposal must be made according to official regulations.

Uncleaned packaging

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number:

ADR, ADN, IMDG, IATA Not applicable

14.2 UN proper shipping name:

ADR, ADN, IMDG, IATA Not applicable

14.3 Transport hazard class(es):

ADR, ADN, IMDG, IATA

Class: Not applicable

14.4 Packing group:

ADR, IMDG, IATA Not applicable 14.5 Environmental hazards: Not applicable.

Marine pollutant: No

14.6 Special precautions for user: Not applicable.

14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code: Not applicable.

Transport/Additional information: Avoid direct sunlight. Make sure of no damage, corrosion, leaks on

the receptacles.

Take necessary measures for preventing cargo shift.

UN "Model Regulation": Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

Labelling according to Regulation (EC) No 1272/2008 Not applicable

Hazard pictograms Not applicable Signal word Not applicable

Hazard statements Not applicable

National regulations No further information available.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

The product is for the industrial use only. We do not guarantee the safety in case the product is used for the other purposes. When using the product for health-care application or food/feed application, consult us in advance. This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific

product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: SAFETY&ENVIRONMENT DEPT.

Contact: http://www.daikinchem.com.cn

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic



Printing date 11.12.2019 Version number 1 Revision: 11.12.2019

Trade name: DAI-EL G-522,G-551,G-556,G-557,G-558,G-565

vPvB: very Persistent and very Bioaccumulative

^{*} Data compared to the previous version altered.