

Revision: 17.09.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: <u>DEMNUM S-20, S-65, S-200</u> Article number: DMS **1.2 Relevant identified uses of the substance or mixture and uses advised against:** No further relevant information available.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: DAIKIN INDUSTRIES, LTD. CHEMICALS DIVISION: Umeda Center Bldg., 4-12, Nakazaki-Nishi 2-chome, Kita-Ku, Osaka, JAPAN Phone: (+81) 6-6373-4345 Fax: (+81) 6-6373-4281

Further information obtainable from: http://www.daikin.com/ *1.4 Emergency telephone number: Japan:* +81-6-6349-7521 *China:* +86-512-5-232-0949, +86-21-34151689 *South Korea:* +82-2-568-1722 *Americas:* +1-256-306-5000 *Europe:* +49-211-179 225-0

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 The substance is not classified, according to the CLP regulation.

2.2 Label elements Labelling according to Regulation (EC) No 1272/2008: Not applicable Signal word: Not applicable

SECTION 3: Composition/information on ingredients

Information on ingredients:

Perfluoroalkyl polyether

SECTION 4: First aid measures

4.1 Description of first aid measures
General information: Seek medical treatment.
After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact:
Immediately wash with water and soap and rinse thoroughly.
Remove contaminated clothes immediately.
After eye contact:
Immediately rinse with a lot of water for several minutes. Remove contact lenses if possible. Continue rinsing.
After swallowing: Rinse mouth with water. Do not induce vomitting.
4.2 Most important symptoms and effects, both acute and chronic: No further relevant information available.
4.3 Indication of any immediate medical attention and special treatment needed:
No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media
Suitable extinguishing agents: Use fire extinguishing methods suitable for surrounding conditions.
5.2 Special hazards arising from the substance or mixture:
Formation of toxic gases is possible during heating or in case of fire.
5.3 Advice for firefighters:
Protective equipment:
Wear self-contained breathing apparatus and protective suit.
Do not inhale explosion gases or combustion gases.

> = 99%



Version number 1

Printing date 17.09.2019

Trade name: DEMNUM S-20, S-65, S-200

Wear fully protective suit.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures: Ensure adequate ventilation before entering the area.
Stay on the windward side.
Keep out unauthorized persons.
Wear appropriate protective devices (See Section 8 Exposure Controls/Personal Protection).
Avoid contact with eyes and skin.
Do not swallow the product.
6.2 Environmental precautions: Prevent seepage into sewage system, workpits and cellars.
6.3 Methods and material for containment and cleaning up:

For a small amount of leakage: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders) or collect in an empty container that can be sealed tightly.

For a large amount of leakage: Enclose with banks to avoid outflow. Lead the leakage to a safe place and collect. 6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace. Do not handle until all safety precautions have been read and understood. Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. 7.2 Conditions for safe storage, including any incompatibilities: Storage Requirements to be met by storerooms and receptacles: Store in a cool and dry location. Keep containers tightly sealed. Information about storage in one common storage facility: See section 10 for information on incompatible materials. Further information about storage conditions: Store in cool, dry conditions in well sealed receptacle. Protect from heat and direct sunlight. Store containers in a well ventilated area. Store locked up. 7.3 Specific end use(s): No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters Ingredients with limit values that require monitoring at the workplace: Not required.

8.2 Exposure controls
Personal protective equipment
General protective and hygienic measures:
Wash hands before breaks and at the end of work.
Do not eat or drink while working.
Keep away from tobacco products.
Respiratory protection:
Use respiratory protective device with filters for organic and acid gas (or airline respirators in some cases) if formation of toxic gases is possible while the product is heated.

Use respiratory protective device with organic gas cartridge.

Revision: 17.09.2019



Version number 1

Revision: 17.09.2019

Trade name: DEMNUM S-20, S-65, S-200

Protection of hands:



Protective gloves

Material of gloves: Rubber

Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. **Eye protection:**



Safety glasses

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and General Information Appearance Form: Colour: Odour: Odour: Odour threshold: pH-value:	Liquid Colourless Odourless Not determined. No further information available.	
Melting point/freezing point: Initial boiling point and boiling range.	$<-53 \ ^{\circ}C$ No further information available.	
Flash point:	Not applicable.	
Flammability (solid, gas): Ignition temperature:	Not applicable. >600 °C	
Decomposition temperature:	No further information available.	
Auto-ignition temperature: Explosive properties:	>600 $^{\circ}\!\mathcal{C}$ Product does not present an explosion hazard.	
Explosion limits: Lower explosive limit: Upper explosive limit:	No further information available. No further information available.	
Vapour pressure at 20 °C:	0.001 hPa	
Density at 20 °C: Relative density Vapour density Evaporation rate	1.85 g/cm ³ 1.85-1.90 Not determined. Not determined.	
Solubility in / Miscibility with water:	No further information available.	
Partition coefficient: n-octanol/water: Viscosity:		
Dynamic: Kinematic:	Not determined. Not determined.	
9.2 Other information:	No further relevant information available.	
SECTION 10. Stability and reactivity		

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.



Version number 1

Trade name: DEMNUM S-20, S-65, S-200

Revision: 17.09.2019

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

Even at the temperatures reached during the normal hot processing of fluoropolymers, fume that presents a potential health hazard may be generated.

To avoid thermal decomposition do not overheat.

10.3 Possibility of hazardous reactions: No dangerous reactions known under normal conditions of use. 10.4 Conditions to avoid: Keep away from heat, sparks, flame, high temperature.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: Danger of toxic fluorine based pyrolysis products.

SECTION 11: Toxicological information

11.1 Information on toxicological effects Acute toxicity no data LD/LC50 values relevant for classification:

Perfluoroalkyl polyether

Oral LD50 >2000 mg/kg (Rat) Dermal LD50 >2000 mg/kg (Rat) Primary irritant effect Skin corrosion/irritation

Perfluoroalkyl polyether

Irritation of skin Primary skin irritation study No irritation (Rabbit)

Irritation of eyes Primary eye irritation study No irritation (Rabbit) Based on available data, the classification criteria are not met. Serious eye damage/irritation Based on available data, the classification criteria are not met. Respiratory or skin sensitisation

Perfluoroalkyl polyether

Sensitisation Skin Sensitization (Guinea pig) No skin sensitization

Based on available data, the classification criteria are not met. Other information (about experimental toxicology): Chromosomal Aberration Study in vitro- Negative CMR effects Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met. STOT-single exposure Based on available data, the classification criteria are not met. STOT-repeated exposure Based on available data, the classification criteria are not met. Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity Aquatic toxicity:

Perfluoroalkyl polyether

NOEL 102 mg/l (Alga) 72 hr > 100 mg/l (Daphnia) 48 hr > 100 mg/l (Fish) Zebra fish 96 hr 12.2 Persistence and degradability: No further relevant information available. Other information:

The product is slightly biodegradable. Activated Sludge, Respiration Inhibition NOEC > 1000 mg/L 12.3 Bioaccumulative potential: No further relevant information available.



Version number 1

Revision: 17.09.2019

Trade name: DEMNUM S-20, S-65, S-200

12.4 Mobility in soil: No further relevant information available.
Ecotoxical effects: no data
12.5 Results of PBT and vPvB assessment
PBT:
No further relevant information available.
Not applicable.
vPvB:
No further relevant information available.
Not applicable.
12.6 Other adverse effects: No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods Recommendation: Disposal must be made according to official regulations.

Uncleaned packaging

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number:	
ADR, ADN, IMDG, IATA 14.2 UN proper shipping name:	Not applicable
ADR, ADN, IMDG, IATA	Not applicable
14.3 Transport hazard class(es):	
ADR, ADN, IMDG, IATA	
Class:	Not applicable
14.4 Packing group:	
ADR, IMDG, IATA	Not applicable
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user:	Not applicable.
14.7 Transport in bulk according to Anne	x II of
MARPOL73/78 and the IBC Code:	Not applicable.
Transport/Additional information:	Avoid direct sunlight. Make sure of no damage, corrosion, leaks on
	the receptacles.
	Take necessary measures for preventing cargo shift.
UN "Model Regulation":	Not applicable
$\mathbf{C} \mathbf{D} \mathbf{C} \mathbf{T} \mathbf{C} \mathbf{N} 1 \mathbf{f} \mathbf{D} 1 \mathbf{f} \mathbf{V} \mathbf{f} \mathbf{f}$	· •

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Labelling according to Regulation (EC) No 1272/2008 Not applicable
Hazard pictograms Not applicable
Signal word Not applicable
Hazard statements Not applicable
15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

The product is for the industrial use only. We do not guarantee the safety in case the product is used for the other purposes. When using the product for health-care application or food/feed application, consult us in advance. This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: EHS Department

Contact: http://www.daikin.com/

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods



Version number 1

Revision: 17.09.2019

Trade name: DEMNUM S-20, S-65, S-200

IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

* Data compared to the previous version altered.